

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2003-097385

(43)Date of publication of application : 03.04.2003

(51)Int.Cl.

F02M 59/44
F02M 59/02

(21)Application number : 2001-291229

(71)Applicant : TOYOTA MOTOR CORP

(22)Date of filing : 25.09.2001

(72)Inventor : ITO YOSHIHIKO


(54) HIGH-PRESSURE PUMP

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a high-pressure pump which suppresses any stepped wear of a side surface of a plunger.

SOLUTION: A pump chamber 14 is formed in a housing 12 of a high-pressure fuel pump. In the cylinder 13, the plunger 16 is supported in a plunger sliding hole 13a in a reciprocatively slidable manner in the axial direction. At a boundary part of the plunger sliding hole 13a and the pump chamber 14, a storage recessed part 32 to surround the plunger 16 is formed, and an elastically deformable annular member 33 to slidably guide the plunger 16 is disposed in the storage recessed part 32.

An inner circumferential surface 32a of the storage recessed part 32 is arc-shaped in the axial direction of the plunger sliding hole 13a, and an outer circumferential surface 33a of the annular member 33 forms an arc-shape along the inner circumferential surface 32a of the storage recessed part 32.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than
the examiner's decision of rejection or
application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's
decision of rejection]

[Date of requesting appeal against examiner's
decision of rejection]

[Date of extinction of right]